

DESCRIPTION

GenFlex Termination Caulk is a one-part polyurethane moisture-curing sealant. It can be used as an exterior sealant on termination bars or used to caulk sheet metal, masonry, concrete block or as a fastener sealer over fastener heads per GenFlex specifications and details. This product is NOT intended to be used as a seam sealant.

PHYSICAL PROPERTIES

PROPERTY	TYPICAL VALUES
Base	Polyurethane
Color	Grey
Solids	92.5 % +/- 2
Tooling Time	Less than 20 minutes
UV & Ozone Resistance	Excellent
Specific Gravity	1.186 +/- 0.024
Cure Systems	Moisture Activated

INSTALLATION

1. Apply Termination Caulk only on clean, dry surfaces in accordance with GenFlex specifications and details. Surfaces onto which the sealant is used shall be free from loose concrete, stone, mortar, foreign materials, and other contaminants.
2. Use Termination Caulk to assure watertight seal between the Termination Bar and parapet wall.
3. Apply sealant into the reservoir channel creating a 100% seal between the termination bar and the wall.
4. Termination Caulk can be applied directly from the cartridge using a standard hand gun.
5. Apply Termination Caulk to substrates above 40° F (4° C).

PRODUCT DATA

SIZE	CONTENTS	PRODUCT #
300 ml (10 oz.) Cartridge	12 Cartridges/Carton	W590010172

COVERAGE RATE

A 300 ml (10 oz.) cartridge seals 24 linear feet in a ¼" x ¼" joint.

CLEAN UP

Use mineral spirits or GenFlex Cleaner while material is fresh. After Termination Caulk cures, it can be removed by abrasion or mechanical means.

LEED INFORMATION

Recycled Content	
Post Consumer	0%
Post Industrial	0%
V.O.C. Content	111 g/L



STORAGE

Store indoors in original unopened containers at a temperature between 60°F and 80°F (16°C and 27°C) for maximum shelf life. Do not store on roof in direct sunlight. When exposed to lower temperatures, restore to room temperature prior to use.

SHELF LIFE

12 months; shelf life will be shortened if exposed to elevated temperatures.

PRECAUTIONARY DATA

- Use with adequate ventilation.
- Avoid prolonged breathing of vapors.
- Avoid prolonged and repeated contact with skin.
- Store at temperature of 80°F (27°C) or below for maximum shelf life.
- Keep out of reach of children.
- Keep away from eyes.
- Do not thin.
- Review Material Safety Data Sheet prior to use.