

## GENFLEX FLEXGUARD™ PEEL & STICK™ WALKWAY PAD

### Item Description

30" X 30" X 5/16"  
(762 mm X 762 mm X 7.9 mm)

### Item Number

W590010121



### Product Information

FlexGuard Peel & Stick Walkway Pads are high quality walkway pads with Peel & Stick tape adhesive factory laminated to the bottom. They help protect the membrane from rooftop foot traffic. The material incorporates excellent levels of hardness, tensile strength, tear resistance, wear, and displays excellent cold flexibility.

The owner is responsible for maintaining walkways in the following areas:

- At all rooftop access points (ladders, hatches, doorways, etc.)
- Around all roof-mounted mechanical equipment requiring maintenance.
- Roofs subjected to traffic more frequently than once a month

### Description

Typical Properties		
Property	Test Method	Typical Values
Pad Dimensions	N/A	30" X 30" X 5/16" (762 mm X 762 mm X 7.9 mm)
Ultimate Elongation	ASTM D 412	80%
Tensile Strength	ASTM D 412	490 psi (3379 kPa)
Tear Resistance	ASTM D 624	117 lb/in (20.5 kN/m)
Specific Gravity	ASTM D 297	1.15
Shore A Durometer	ASTM D 4220	60

### Installation

1. Membrane to receive tape portion of walkway pad shall be free from dust, dirt, and other contaminants. Clean contaminated surfaces with a clean rag using appropriate GenFlex Splice Cleaner.
2. Apply GenFlex Primer in an even coat using Scrub Pad & handle on the membrane to receive tape and underside perimeter area of walkway pad and allow to thoroughly dry before proceeding.
3. Place walkway pad into position on primed membrane and remove release paper from the tape.
4. Press pad firmly into place on primed membrane and roll with steel or silicone roller.

### Precautions

GenFlex FlexGuard Peel & Stick Walkway Pads should not be applied over a field fabricated seam.

**Product Data**

Size	Quantity	Product #
30" X 30" X 5/16" (762 mm X 762 mm X 7.9 mm)	50 Pads per Pallet	W590010121

**\*LEED® Information**

Recycled Content

Post Consumer 0%

Post Industrial 0%

\*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

**Storage**

Store in original unopened container indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C). Do not store on roof in direct sunlight or at temperatures above 80 °F (27 °C). When exposed to lower temperatures, restore to room temperature prior to use.

**Shelf Life**

24 months; shelf life will be shortened if exposed to elevated temperatures.

**Precautionary Data**

Take care when moving, transporting, and handling, etc., to avoid sources of punctures and physical damages.

Isolate waste products such as petroleum products, greases, oils (mineral and vegetable), and animal fats from the GenFlex membrane.

Contact GenFlex Roofing Systems Technical Department for specific recommendations.

Assure the structural decking will support the loads incurred by the material stored on roof top. The deck load limitations should be specified by the project designer.

Refer to Safety Data Sheet for additional information.

Please contact Quality Building Services Technical Department at 1-800-443-4272 option 1, for further information.

*This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.*