

GENFAST™ LITE DECK FASTENER

Item Description	Item Number	Item Description	Item Number
2 5/8" (67 mm)	W590055222	8" (203 mm)	W590055228
3" (76 mm)	W590055223	9" (229 mm)	W590055229
4" (102 mm)	W590055224	10" (254 mm)	W590055230
5" (127 mm)	W590055225	12" (305 mm)	W590055231
6" (152 mm)	W590055226		
7" (178 mm)	W590055227		

Product Information

Description

GenFlex GenFast™ Lite Deck Fasteners are specifically designed to be used in roofing applications for the attachment of insulation to cementitious wood fiber (i.e. Tectum), gypsum, or Lightweight concrete decks. GenFast Lite Deck Fasteners are available in various lengths from 2 5/8" to 12" (67 mm to 305 mm).

GenFast Lite Deck Fasteners are manufactured with a deep, coarse thread design providing excellent pull-out resistance. Insulation attachment is to be with the 3" (76 mm) GenFast Lite Deck Plate. Membrane attachment is to be with the GenFast Anchor Bar.

Typical Properties	
Screw Property	Typical Values
Metal	CR-10 Coated Steel
Color	Black
Thread Diameter	0.375" (9.5 mm)
Shank Diameter	0.310" (7.9 mm)
Head Style	#3 Phillips Flat Head
Head Diameter	0.710" (18 mm)

Installation

Minimum required embedment for GenFlex GenFast Lite Deck Fasteners is 2" (51 mm) into the deck.

- Cementitious Wood Fiber Decks: Position and drive the fastener through the plate into the deck.
- Gypsum or Light Weight Concrete: A pilot hole is required. The pilot hole should be 1/2" (13 mm) deeper than the required embedment into the deck. The diameter of the pilot hole is determined by the pullout values achieved.

Check current GenFlex Specifications for exceptions and/or changes.

Product Data

Screw Length	Thread Length	Pieces/Carton
2 5/8" (67 mm)	Full	500
3" (76 mm)	Full	500
4" (102 mm)	3" (76 mm)	500
5" (127 mm)	3" (76 mm)	250
6" (152 mm)	3" (76 mm)	250
7" (178 mm)	3" (76 mm)	250
8" (203 mm)	3" (76 mm)	250
9" (229 mm)	3" (76 mm)	125
10" (254 mm)	3" (76 mm)	125
12" (305 mm)	3" (76 mm)	125

***LEED® Information**

Recycled Content:

Post-Consumer: 0%

Pre-Consumer 0%

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Storage

Fasteners should be protected from moisture and kept dry at all times.

If stored out of doors, place on skids in a dry area and cover with a breathable tarp.

Precautionary Data

- Eye protection is recommended when installing fasteners and plates.
- Do not overdrive the fasteners as this will significantly reduce the fastener and plate performance and/or cause the fasteners to strip out.
- Refer to Safety Data Sheet (SDS) for further information.

Please contact GenFlex Technical Services at 1-800-443-4272 option 1, for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.