

**GenFast™ 2 3/8" WH Seam Plate**

**DESCRIPTION**

GenFast™ WH Seam Plates are specifically designed to be used with GenFast #15 WH fasteners to attach GenFlex TPO membranes to a variety of approved substrates including 22-gauge steel, wood or structural concrete decks.

**PHYSICAL PROPERTIES**

PROPERTY	MINIMUM PERFORMANCE
Metal	AZ 55 Galvalume®
Diameter	2 3/8" (60.3 mm)
Thickness	20 Gauge (.037")
Hole Diameter	.265" ± .003 (6.73 mm ± .076 mm)
Corrosion Resistance	Meets FM requirements – Less than 15% red rust in 15 cycles of Kesternich Testing (DIN 50018)
Number of Eyehooks™	Total of 8 (4 inner and 4 outer extensions)

**INSTALLATION**

The plates are positioned within the seam area as required by current GenFlex TPO specifications with the Eyehooks™ against the membrane. Once placed in the correct seam location, attach the plate through the membrane and roof assembly into the deck using a GenFlex #15 WH Fastener using a screw gun.

Care should be taken not to overdrive or under drive the fastener and plate assembly within the seam area.

**PRODUCT DATA**

PRODUCT #	QUANTITY
W590051003	1000 per bucket



**LEED INFORMATION**

Recycled Content	
Post Consumer	0%
Post Industrial	21%

**STORAGE**

Fasteners should be protected from moisture and kept dry at all times. If stored out of doors, place on skids in a dry area and cover with a breathable tarp.

**SHELF LIFE**

Not applicable

**PRECAUTIONARY DATA**

Eye protection is recommended when installing fasteners and plates.

Seam Plates are manufactured from galvanized metal. Precautions should be taken to avoid metal slivers, etc.

Refer to Material Safety Data Sheet for additional information.

Note: Galvalume® is a registered trademark of BIEC International Inc. Eyehook™ is a trademark of OMG, Inc.