

GenFlex TPO Non-Reinforced Flashing

Item Description

1 Roll – White
 1 Roll – Tan
 1 Roll – Gray

Item Number

W590030080
 W590030222
 W590030221



Product Information

Description

GenFlex TPO Non-Reinforced Flashing is a .060" (1.52 mm) flexible non-reinforced thermoplastic flashing material designed to be used where pre-molded or reinforced accessories cannot be utilized. GenFlex TPO Non-Reinforced Flashing is available in white, tan and gray.

Typical Properties		
Property	Test Method	Typical Values
Color	N/A	White, Tan, Gray
Thickness, Nominal	ASTM D 412	0.060" (1.52 mm)
Weight per Roll	N/A	27.6 lb (12.5 kg)
Tensile, min.	ASTM D 412	1500 psi (10.3 MPa)
% Elongation at Break	ASTM D 412	500%
Tear Strength	ASTM D 624, Die C	300 lbf/in (52.3kN/m)
Zenon Arc	ASTM G 151 ASTM G 155	Pass Pass
QUV	ASTM G 151 ASTM G154	Pass Pass

Installation

1. Please consult current GenFlex TPO specifications and details for specific heat welding applications.
2. Substrates must be clean, dry, smooth, free of sharp edges, fins, loose or foreign materials, oil, grease, and other materials which may damage the flashing.
3. All roughened surfaces which could damage the flashing shall be repaired as specified to offer a smooth substrate.
4. All surface voids greater than 0.25" (6.35 mm) wide shall be properly filled with an acceptable fill material.

Product Data

Roll Size	Quantity	Color	Product Number
24" x 50' (609.6 mm x 15.24 m)	1 Roll (30 Rolls/Pallet)	White Tan Gray	W590030080 W590030222 W590030221

***LEED® Information**

Recycled Content

Post Consumer 0%

Post Industrial 0%

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Storage

- Store in original unopened container indoors at store on roof in direct sunlight or at temperatures above to room temperature prior to use.
- Do not store in direct sunlight or at temperatures above 80 °F (27 °C).
- When exposed to lower temperatures, restore to room temperature prior to use.

Shelf Life

Not applicable

Precautionary Data

- Take care when moving, transporting, and handling, etc. to avoid sources of punctures and physical damage.
- Contact GenFlex Systems Technical Department for specific recommendations.
- Refer to Material Safety Data Sheet for additional information.

Please contact GenFlex Technical Services at 1-800-443-4272 option 1, for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.