

FLEXWHITE™ EDGE CAULK

Item Description

11 oz (326 mL) Tube

Item Number

W590030105



Product Information

Description

GenFlex FlexWhite Edge Caulk is a high quality one-part elastomeric sealant that is used primarily to seal FlexWhite lap edges. It offers excellent adhesion to both EPDM and TPO membranes and has excellent weathering resistance to ozone and ultra-violet light.

| Typical Properties | |
|-------------------------|--|
| Property | Typical Values |
| Color | White |
| Base | EPDM Rubber |
| Solvents | Light Aliphatic Naphtha |
| Solids | 80% (minimum) |
| Weight | 8.7 ± 0.05 lb/gal (1.04 ± 0.06 kg/L) |
| Viscosity/Extrudability | Press Flow: Extrude 20 grams in 25-65 seconds through Press Flow apparatus under 40 psi pressure |
| V.O.C. Content 250 g/L | 250 g/L |

Installation

IMPORTANT: Ensure the receiving surfaces are free of debris and no moisture.

1. Apply GenFlex FlexWhite Edge Caulk at a coverage rate of 15 feet (4.6 m) of 3/8" x 1/4" (9.5 mm x 6.3 mm) continuous bead per tube, per current GenFlex specifications and details.
2. Apply a continuous "high profile" bead of FlexWhite Edge Caulk to the entire outside edge of the FlexWhite Peel & Stick flashing products (FlexWhite Corners, T-Joints, Cover Tape, etc.).
3. GenFlex FlexWhite Edge Caulk may be used at other details using Cover Tape, including curb or skylights, pitch pans, scuppers, perimeter edge metal, and gutters.
4. Refer to current GenFlex Technical Specifications for additional application instructions.

Product Data

| Size | Contents | Product # |
|---------------------|---------------------|------------|
| 11 oz (326 mL) tube | 12 tubes per carton | W590030105 |

Coverage Rate: 15' (4.6 m) per tube

***LEED® Information**

Recycled Content:

Post Consumer 0%

Post Industrial 0%

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Storage

Store indoors in original unopened containers at a temperature between 60 °F and 80 °F (16 °C and 27 °C) for maximum shelf life. Do not store on roof in direct sunlight. When exposed to lower temperatures, restore to room temperature prior to use.

Shelf Life

24 months; shelf life will be shortened if exposed to elevated temperatures.

Precautionary Data

This product is extremely flammable. Vapors may cause flash fires. Vapors may ignite explosively under certain conditions. Keep away from fire, sparks, and sources of heat. Extinguish all flames and pilot lights. Turn off electronic motors, stoves, or heaters, or any source of ignition during use and until all vapors have been dispersed. Do not smoke.

Close containers after use.

Use with adequate ventilation.

Avoid prolonged breathing of vapors.

Avoid prolonged and repeated contact with skin.

Store at temperature of 80 °F (27 °C) or below for maximum shelf life.

Keep out of reach of children.

Keep away from eyes.

Use chemically resistant gloves when handling.

Review Safety Data Sheet prior to use.

Please contact Quality Building Services Technical Department at 1-800-443-4272 option 1, for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.