

GENFAST™ TERMINATION BAR

Item Description

1.25" (32 mm) x 10" (3 m)
1.25" (32 mm) x 5" (1.5 m)

Item Number

W590010088
W590051239



Product Information

Description

GenFast Termination Bar is a corrosion resistant aluminum material used for terminating and sealing membrane wall flashings to various approved substrates as outlined by current GenFlex Specifications and Details.

Typical Properties	
Property	Typical Values
Material	Corrosion Resistant Aluminum
Thickness	0.090"(2.3 mm)
Features	GenFlex logo on each section Reservoir channel for Termination Caulk on top
Holes	Pre-punched 0.28" x 0.38" (7 mm x 10 mm) Slotted Holes 3.93" (100 mm) o.c.

Installation

Refer to current GenFlex Technical Specifications for additional instructions.

1. Substrates must be free from dust, dirt, oil, water, and other contaminants (wall areas above termination bar must not pass water). Install per current GenFlex specifications.
2. Apply GenFlex WaterStop behind flashing membrane.
3. Install flat side of bar towards flashing so "lip" is facing upwards and forms a wide reservoir for edge caulk.
4. Anchor bar through pre-punched holes at a rate to maintain a seal to the wall against WaterStop - Max. 12" o.c. (304.8 mm).
5. Remove excess flashing material above bottom of lap sealant reservoir channel.
6. Install GenFlex Termination Caulk into reservoir channel.

Application Precautions

- Do not use as a bar anchor.
- Where field cutting is necessary, remove any burrs from bar.
- Clean up shavings, etc., that may occur from field cutting.
- Install flat side of bar towards flashing so "lip" is facing upwards and forms a wide reservoir for edge caulk.
- Keep a space of ¼" (6 mm) between each length of GenFlex Termination Bar.
- GenFlex Termination Bars must be installed directly to the wall surface, not existing sheet metal, flashings, etc.
- Install GenFlex Termination Bar on hard, smooth surfaces only. Do not install on substrates where seal is lost at mortar joints, etc.
- Install GenFlex Termination Bar Vertically where base flashing(s) end.
- Do not install GenFlex Termination Bar to wood or other porous surfaces.
- At inside and outside corners, GenFlex Termination Bar must be cut and continued.
- GenFlex Termination Bar must be fastened a max. of 1" (25 mm) from each end of all sections.

Product Data

50 Bars per Tube

*LEED® Information

Recycled Content

Post Consumer 0%

Post Industrial 0%

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Storage

Termination Bar should be protected from moisture and kept dry at all times. If stored out of doors, place on skids in a dry area and cover with a breathable tarp.

Precautionary Data

- Eye protection is recommended when installing the appropriate fastener through the Termination Bar.
- Refer to Safety Data Sheet for additional information.

Please contact GenFlex Technical Services at 1-800-443-4272 option 1, for further information.

This sheet is meant to highlight GenFlex products and specifications and is subject to change without notice. GenFlex takes responsibility for furnishing quality materials which meet published GenFlex product specifications. Neither GenFlex nor its representatives practice architecture. GenFlex offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. GenFlex accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No GenFlex representative is authorized to vary this disclaimer.