

Product Data Sheet

GENFAST™ #14 PREASSEMBLED SCREW AND PLATE



Description

GenFast™ #14 Preassembled Screws and Plates may be used in any GenFlex system for attachment of roofing insulations to steel, wood, and lightweight concrete (into steel deck) substrates.

Item Number:

- 9" W590055123
- 10" W590055124
- 11" W590055125
- 12" W590055126
- 14" W590055127


Physical Properties

SCREW PROPERTIES	MINIMUM PERFORMANCE
Metal	SAE 1022 Heat Treated
Diameter and Thread	#14 Modified Buttress
Head Style	#3 Phillips
Corrosion Coating	SPEX™
Fastener Tip	Patented X-Point

PLATE PROPERTIES	MINIMUM PERFORMANCE
Material	Polypropylene
Diameter	3" (76mm) round
Corrosion Coating	Non-corrosive plastic

Method of Application

- GenFast #14 Preassembled Screw length is determined as follows:
 - Steel Deck – Minimum of 1" (25 mm) required penetration
 - Wood Deck – Minimum of 1" (25 mm) required penetration
- Check current GenFlex specifications for exceptions and/or changes.



Product Data

SCREW LENGTH	THREAD LENGTH	PIECES/CARTON
9"	4"	250
10"	4"	200
11"	4"	200
12"	4"	200
14"	4"	150

Compliance:

Recycled Content:

Post Consumer: 25%

Pre Consumer: 0%

Storage:

Fasteners should be protected from moisture and kept dry at all times.

If stored out of doors, place on skids in a dry area and cover with a breathable tarp.

Precautions:

Eye protection is recommended when installing fasteners and plates.

Refer to Material Safety Data Sheet for further information.