

Product Data Sheet

GENFAST™ #15 PREASSEMBLED SCREW AND PLATE



Description

GenFast™ #15 Preassembled Screws and Plates may be used in any GenFlex system or attachment of roofing membrane to steel, OSB (with acceptable pull test) and plywood.

Item Number:

2" W590055141

3" W590055142

4" W590055143

5" W590055144

6" W590055145

7" W590055146

8" W590055147

10" W590055148

12" W590055149

Physical Properties

SCREW PROPERTIES	MINIMUM PERFORMANCE
Metal	SAE 1022 Heat Treated
Diameter and Thread	0.435" Diameter Head and 0.265 Diameter Thread
Head Style	#3 Phillips Truss Head
Corrosion Coating	CR-10
Fastener Tip	Drill Point

PLATE PROPERTIES	MINIMUM PERFORMANCE
Material	AZ 55 Galvalume®
Diameter	2-7/8" (60.3 mm) round
Corrosion Coating	Meets FM requirements – less than 15% red rust in 15 cycles of Kesternich Testing (DIN 50018)



Method of Application

1. GenFast #15 Preassembled Screw length is determined as follows:
 - Steel Deck – Minimum of 1" (25 mm) required penetration
 - Wood Deck – Minimum of 1" (25 mm) required penetration
2. Check current GenFlex specifications for exceptions and/or changes.

Product Data

SCREW LENGTH	THREAD LENGTH	PIECES/ CARTON
2"	Full	250
3"	Full	250
4"	3"	250
5"	4"	250
6"	4"	250
7"	4"	250
8"	4"	250
10"	4"	200
12"	4"	200

Compliance

Recycled Content

Post Consumer	25%
Pre Consumer	0%



Product Data Sheet

GENFAST™ #15 PREASSEMBLED SCREW AND PLATE



Storage

Fasteners should be protected from moisture and kept dry at all times.

If stored out of doors, place on skids in a dry area and cover with a breathable tarp.

Precautionary Data

Eye protection is recommended when installing fasteners and plates.

Refer to Material Safety Data Sheet for further information.