

Flat Polyiso Insulation

All GenFlex Polyiso insulations have a polyisocyanurate foam core. The standard compressive strength is 20 psi, but 25 psi is also available, upon request. Different facers are used to make specific products, as described below:

Product Name	Top Side		Bottom Side	
Polyiso Insulation	Black Glass Reinforced Mat		Black Glass Reinforced Mat	
Nail Base	7/16" Oriented Strand Board		Black Glass Reinforced Mat	
HD ISO Composite	HD ISO		Single Glass Coated Facer	
Insulation Thickness*	Pieces Per Bundle	Square Feet Per Bundle 4x8	Square Feet Per Bundle 4x4	Square Feet Per Truckload
1.00	48	1,536	768	36,864
1.50	32	1,024	512	24,576
1.75	27	864	432	20,376
2.00	24	768	384	18,432
2.20	21	672	336	16,128
2.50	19	608	304	14,592
2.60	18	576	288	13,824
3.00	16	512	256	12,288
3.25	14	448	224	10,752
3.30	14	448	224	10,752
3.50	13	416	208	9,984
4.00	12	384	192	9,216

* Non-Standard Sizes Available at 12 Bundle Minimum Order Quantity (4' x 8' Boards)

Tapered Polyiso Insulation

All GenFlex Polyiso insulations have a polyisocyanurate foam core. The standard compressive strength is 20 psi, but 25 psi is also available, upon request. Different facers are used to make specific products, as described below:

Insulation Thickness**	Pieces Per Bundle	Square Feet Per Bundle 4x4	Slope	Max-Min Height Per
AA	64	1,024	1/8" Slope	0.5" - 1.0"
A	38	416	1/8" Slope	1.0" - 1.5"
B	26	416	1/8" Slope	1.5" - 2.0"
C	20	320	1/8" Slope	2.0" - 2.5"
X	48	768	1/4" Slope	.0.5" - 1.5"
Y	24	384	1/4" Slope	1.5" - 2.5"
Q	32	512	1/2" Slope	.0.5" - 2.5"
Z	16	256	1/4" Slope	2.5" - 3.5"

** Non-Standard Sizes Available at 24 Bundle Minimum Order Quantity (4' x 4' Boards)

GenFlex Plant Locations: Connecticut, Florida, Kentucky, Pennsylvania, Texas, Wisconsin, and Utah.



Effective July 1, 2014

Updated 01/16/15

HD ISO Cover Board

Thickness	Item Code	Pieces Per Bundle	Bundles Per Truckload	Square Feet Per Truckload
1/2" - 4' x 4'	W8H-3GG-050I	46	96	70,656
1/2" - 4' x 8'	W8H-3GG-050H	46	48	70,656

Note: Stopover fee of \$100.00 charged for a second delivery destination located within 100 miles of the first delivery point.

Coated Glass Facer Insulation

Coated Glass Facer Insulation is a closed cell polyisocyanurate foam core, bonded chemically to a heavy duty, dimensionally stable, inorganic glass facer. The standard compressive strength is 20 psi, but 25 psi is also available, upon request.

Product Name	Top Side		Bottom Side	
Coated Glass Facer Insulation	Inorganic Double Coated Glass Mat		Inorganic Double Coated Glass Mat	
Insulation Thickness	Pieces Per Bundle	Square Feet Per Bundle 4x8	Square Feet Per Bundle 4x4	Square Feet Per Truckload
1.00*	48	1,536	768	36,864
1.25	38	1,216	608	29,184
1.50*	32	1,024	512	24,576
1.75	27	864	432	20,376
2.00*	24	768	384	18,432
2.30	20	640	320	15,360
2.50*	19	608	304	14,592
2.80	17	544	272	13,056
3.00*	16	512	256	12,288
3.25	14	448	224	10,752
3.50	13	416	208	9,984
3.75	12	384	192	9,216
4.00	12	384	192	9,216

***Note: 1.0", 1.5", 2.0", 2.5", and 3.0" do not have a minimum bundle requirement.**

For all other thicknesses a minimum 24 bundle order is required.

GenFlex Plant Locations: Connecticut, Florida, Kentucky, Pennsylvania, Texas, Wisconsin, and Utah.

Lead times may vary, contact GenFlex Customer Service for lead times.



Effective July 1, 2014

Updated 01/16/15

DensDeck®				
Thickness	Item Code W56RAC...	Pieces Per Bundle	Bundles Per Truckload	Square Feet Per Truckload
1/4" - 4' x 8'	8625	42	28 - 29	37,632 - 38,976
1/2" - 4' x 8'	8650	30	24 - 25	23,040 - 24,000
5/8" - 4' x 8'	8662	30	18 - 19	17,280 - 18,240
DensDeck Prime				
Thickness	Item Code W56RAC...	Pieces Per Bundle	Bundles Per Truckload	Square Feet Per Truckload
1/4" - 4' x 4'	8724	60	40	38,400
1/4" - 4' x 8'	8725	42	28 - 29	37,632 - 38,976
1/2" - 4' x 4'	8754	50	28	22,400
1/2" - 4' x 8'	8750	30	24 - 25	23,040 - 24,000
5/8" - 4' x 4'	8764	40	28	17,920
5/8" - 4' x 8'	8762	30	18 - 19	17,280 - 18,240

DensDeck is a registered trademark of Georgia-Pacific.

SECUROCK® Gypsum Fiber Roof Boards

Thickness	Item Code W56RAC...	Pieces Per Bundle	Weight Per Bundle	Bundles Per Truckload*	Square Feet Per Truckload
1/4" - 4' x 4'	8770	100	2,540	18	28,800
1/4" - 4' x 8'	8766	50	2570	18	28,800
3/8" - 4' x 4'	8771	80	2565	18	23,040
3/8" - 4' x 8'	8767	40	2595	18	23,040
1/2" - 4' x 4'	8772	60	2445	19	18,240
1/2" - 4' x 8'	8768	30	2475	19	18,240
5/8" - 4' x 4'	8733	48	2445	19	14,600
5/8" - 4' x 8'	8769	24	2,475	19	14,590

SECUROCK® Glass Mat Roof Boards

Thickness	Item Code W56RAC...	Pieces Per Bundle	Weight Per Bundle	Bundles Per Truckload*	Square Feet Per Truckload
1/4" - 4' x 8'	8774	42	1,688	28	37,632
1/2" - 4' x 8'	8775	30	1995	24	23,040
5/8" - 4' x 8'	8776	30	2667	18	17,280

*Quantities can vary according to shipping location and should be verified at the time of order placement

*Securock is a registered trademark of USG

GenFlex Wood Fiber Cover Board

Product	Item Code W56358...	Size	Pieces Per Bundle	Square Feet Per Bundle	Weight Per Bundle	Bundles Per Truck	Square Feet Per Truckload
1/2" Wood Fiber "E" (Jarret, VA)	8501	4' x 4'	95	1,520	973	44	66,880
	8502	4' x 8'	95	3,040	1,946	22	66,880
1" Wood Fiber "E" (Jarret, VA)	8504	4' x 4'	48	768	907	44	33,792
	8505	4' x 8'	48	1,536	1,813	22	33,792
1/2" Wood Fiber "B" (Intl' Falls, MN)	8501	4' x 4'	90	1,440	1,140	44	63,360
	8502	4' x 8'	90	2,880	2,300	22	63,360
1" Wood Fiber "B" (Intl' Falls, MN)	8504	4' x 4'	45	720	1,120	44	45,760
	8505	4' x 8'	45	1,440	2,080	22	45,760

Availability: GenFlex Wood Fiber is manufactured in a number of strategically located facilities in order to provide prompt and efficient delivery throughout the United States.

Poly Bagging: All truckloads of Wood Fiber are shipped without poly bagging. Poly bags are available upon request for an additional charge.

Wood Fiber Freight Terms

- Freight allowed on truckload shipments of 1/2" and 1" wood fiber roof insulation for full truckloads only.
- For an additional charge, 1/2" 4' x 8' wood fiber roof insulation is inventoried in some GenFlex insulation plants and may be combined with ISO 95+ for prepaid shipments.
- 1" wood fiber roof insulation is not inventoried at any GenFlex location and is only shipped in full truckload quantities.



Effective July 1, 2014

Updated 01/16/15

ISO Adhesives

Product	Item Number	Size	Quantity	Weight	Approx. Coverage Rates ²
ISO Bond Insulation Adhesive - Part 1	W590052001	5 gal	Bag in a box	50.8 lb / bag	100 - 200 ft ² /gal
ISO Bond Insulation Adhesive - Part 2	W590052002	5 gal	Bag in a box	42.5 lb / bag	100 - 200 ft ² /gal
One Step Insulation Adhesive	W590010132	750 ml Twin Cartridges	4 Cartridges / Carton	20 lb (9.07 kg)	200 - 600 ft ² /gal (4" - 12" bead)

¹Sold in packaged quantities only.

²Coverages are estimated. Actual field application may vary.

³Items available as a direct shipment from vendor

Subject to change without notice.