

REGION			REGION	
TSM:			CSR:	
email:			email:	
Phone:			Phone:	
Fax:			Fax:	

GenFlex Polyiso Insulation Order Form

Sold To:		PO#		DATE	
		DELIVERY DATE			
		24 HOUR CALL#			
Ship To:		CONTACT NAME			
		SPECIAL INSTRUCTIONS			
Tapered Quote #		Quote Version			

GenFlex Flat Polyiso

All GenFlex Polyiso insulations have a polyisocyanurate foam core with black glass reinforced mat facers top and bottom. The standard compressive strength is 20 psi. 25 psi polyisocyanurate is also available for an up charge. Please contact your GenFlex Territory Sales Manager, Customer Service Representative or Distributor for pricing.

Quantity/ Units	20 psi	25 psi	4X4	4X8	Thickness (inches)	Pieces per Bundle	Square Feet per Bundle 4 X 8	Square Feet per Bundle 4 X 4	Square Feet per Truckload
					1.00	48	1,536	768	36,864
					1.50	32	1,024	512	24,576
					1.75	27	864	432	20,376
					2.00	24	768	384	18,432
					2.20	21	672	336	16,128
					2.50	19	608	304	14,592
					2.60	18	576	288	13,824
					3.00	16	512	256	12,288
					3.25	14	448	224	10,752
					3.30	14	448	224	10,752
					3.50	13	416	208	9,984
					4.00	12	384	192	9,216

Add non-standard thickness orders here:

GenFlex Tapered Polyiso

Quantity/ Units	20 psi	25 psi	4X4	Thickness (inches)	Pieces per Bundle	Square Feet per Bundle 4 X 4	Slope	Max-Min Height Per
				AA	64	1,024	1/8" Slope	0.5" - 1.0"
				A	38	608	1/8" Slope	1.0" - 1.5"
				B	26	416	1/8" Slope	1.5" - 2.0"
				C	20	320	1/8" Slope	2.0" - 2.5"
				X	48	768	1/4" Slope	.0.5" - 1.5"
				Y	24	384	1/4" Slope	1.5" - 2.5"
				Q	32	512	1/2" Slope	.0.5" - 2.5"
				Z	16	256	1/4" Slope	2.5" - 3.5"

Add non-standard thickness orders here:

GenFlex HD Polyiso Cover Boards

GenFlex 1/2" standard iso cover board has a foam core with black glass reinforced mat facers top and bottom. The standard compressive strength is 20 psi, but 25 psi is also available for an upcharge. GenFlex 1/2" HD ISO cover board has a high density foam core with coated glass facers top and bottom. The standard compressive strength is 120 psi. Contact GenFlex Territory Sales Manager, Customer Service Representative or Distributor for pricing.

Quantity/ Units	20 psi	25 psi	4X4	4X8	Thickness (inches)	Pieces per Bundle	Square Feet per Bundle 4 X 8	Square Feet per Bundle 4 X 4	Square Feet Per Truckload
					HD 1/2"	46	1,472	736	70,656
					Standard 1/2"	46	3,072	1,536	73,728

The most commonly used tapered panels are listed here. GenFlex Tapered Polyiso is available in 1/3", 1/4", 1/8", 1/16" and 3/16" slopes per foot and in 4' x 4' panels. For more information please contact your GenFlex Territory Sales Manager.

Add non-standard thickness orders here:

GenFlex Nail Base

GenFlex Nail Base has top side consisting of 7/16" Oriented Strand Board and a bottom side consisting of Black Glass Reinforced Mat. All GenFlex Polyiso insulations have a polyisocyanurate foam core with black glass reinforced mat facers top and bottom. The standard compressive strength is 20 psi. 25 psi polyisocyanurate is also available for an up charge. Please contact your GenFlex Territory Sales Manager, Customer Service Representative or Distributor for pricing.

Quantity/ Units	20 psi	25 psi	4X4	4X8	Thickness (inches)	Pieces per Bundle	Square Feet per Bundle 4 X 8	Square Feet per Bundle 4 X 4	Square Feet per Truckload
					1.00	48	1,536	768	36,864
					1.25	38	1,216	608	29,184
					1.50	32	1,024	512	24,576
					1.75	27	864	432	20,376
					2.00	24	768	384	18,432
					2.30	20	640	320	15,360
					2.50	19	608	304	14,592
					2.80	17	544	272	13,056
					3.00	16	512	256	12,288
					3.25	14	448	224	10,752
					3.50	13	416	208	9,984
					3.75	12	384	192	9,216
					4.00	12	384	192	9,216

Add non-standard thickness orders here:

GenFlex HD ISO Composite

GenFlex Composite consists of polyisocyanurate foam core with black glass reinforced mat facers top and bottom, joined with a high density foam core with coated glass facers top and bottom. All GenFlex Polyiso insulations have a polyisocyanurate foam core with black glass reinforced mat facers top and bottom. The standard compressive strength is 20 psi. 25 psi polyisocyanurate is also available for an up charge. Please contact your GenFlex Territory Sales Manager, Customer Service Representative or Distributor for pricing.

Quantity/ Units	20 psi	25 psi	4X4	4X8	Thickness (inches)	Pieces per Bundle	Square Feet per Bundle 4 X 8	Square Feet per Bundle 4 X 4	Square Feet per Truckload
					1.00	48	1,536	768	36,864
					1.25	38	1,216	608	29,184
					1.50	32	1,024	512	24,576
					1.75	27	864	432	20,376
					2.00	24	768	384	18,432
					2.30	20	640	320	15,360
					2.50	19	608	304	14,592
					2.80	17	544	272	13,056
					3.00	16	512	256	12,288
					3.25	14	448	224	10,752
					3.50	13	416	208	9,984
					3.75	12	384	192	9,216
					4.00	12	384	192	9,216

Add non-standard thickness orders here:

GenFlex Coated Glass Facer Insulation

GenFlex Coated Glass Facer is a closed cell polyisocyanurate foam core, bonded chemically to a heavy duty, dimensionally stable, inorganic glass facer. The standard compressive strength is 20 psi.

Quantity/ Units	20 psi	25 psi	4X4	4X8	Thickness (inches)	Pieces per Bundle	Square Feet per Bundle 4 X 8	Square Feet per Bundle 4 X 4	Square Feet per Truckload
					1.00	48	1,536	768	36,864
					1.25	38	1,216	608	29,184
					1.50	32	1,024	512	24,576
					1.75	27	864	432	20,376
					2.00	24	768	384	18,432
					2.30	20	640	320	15,360
					2.50	19	608	304	14,592
					2.80	17	544	272	13,056
					3.00	16	512	256	12,288
					3.25	14	448	224	10,752
					3.50	13	416	208	9,984
					3.75	12	384	192	9,216
					4.00	12	384	192	9,216

Add non-standard thickness orders here:

ISO Adhesives

Quantity/ Units	Product	Item Code	Size	Unit
	ISO Bond Insulation Adhesive - Part 1	W590052001	5 gal	Bag in a box
	ISO Bond Insulation Adhesive - Part2	W590052002	5 gal	Bag in a box
	One Step Insulation Adhesive	W590010132	750 ml Twin Cartridges	4 crtg/carton

DensDeck®

Quantity/ Units	Thickness	Item Code W56RAC...	Pieces Per Bundle	Bundles Per Truckload	Square Feet per Truckload
	1/4" - 4' x 8'	8625	42	28 - 29	37,632 - 38,976
	1/2" - 4' x 8'	8650	30	24 - 25	23,040 - 24,000
	5/8" - 4' x 8'	8662	30	18 - 19	17,280 - 18,240

DensDeck Prime

Quantity/ Units	Thickness	Item Code W56RAC...	Pieces Per Bundle	Bundles Per Truckload	Square Feet per Truckload
	1/4" - 4' x 4'	8724	60	40	38,400
	1/4" - 4' x 8'	8725	42	28 - 29	37,632 - 38,976
	1/2" - 4' x 4'	8754	50	28	22,400
	1/2" - 4' x 8'	8750	30	24 - 25	23,040 - 24,000
	5/8" - 4' x 4'	8764	40	28	17,920
	5/8" - 4' x 8'	8762	30	18 - 19	17,280 - 18,240

DensDeck is a registered trademark of Georgia-Pacific.

*1/4" Dens-Deck is available in select ISO plants and may be combined with Polyiso orders.

SECURROCK® GYPSUM FIBER ROOF BOARDS

Quantity/ Units	Thickness	Item Code W56RAC...	Pieces Per Bundle	Weight Per Bundle	Bundles Per Truckload*	Square Feet per Truckload
	1/4" - 4' x 4'	8770	100	2,540	18	28,800
	1/4" - 4' x 8'	8766	50	2,570	18	28,800
	3/8" - 4' x 4'	8771	80	2,565	18	23,040
	3/8" - 4' x 8'	8767	40	2,595	18	23,040
	1/2" - 4' x 4'	8772	60	2,445	19	18,240
	1/2" - 4' x 8'	8768	30	2,475	19	18,240

	5/8" - 4' x 4'	8733	48	2,445	19	14,600
	5/8" - 4' x 8'	8769	24	2,475	19	14,590

SECURROCK® GLASS MAT ROOF BOARDS

Quantity/ Units	Thickness	Item Code W56RAC...	Pieces Per Bundle	Weight Per Bundle	Bundles Per Truckload*	Square Feet per Truckload
	1/4" - 4' x 8'	8774	42	1,688	28	37,632
	1/2" - 4' x 8'	8775	30	1,995	24	23,040
	5/8" - 4' x 8'	8776	30	2,667	18	17,280

*Quantities can vary according to shipping location and should be verified at the time of order placement

*Securock is a registered of USG

STRUCTODEK® HD with Primed Red Coating

Quantity/ Units	Size	Item Code	Pieces Per Bundle	Weight Per Bundle	Bundles Per	Square Feet per
	4' x 4'	W563588531	90	1,000	48	69,120
	4' x 8'	W563588532	90	2,000	24	69,120

*Quantities can vary according to shipping location and should be verified at the time of order placement

*Structodek is a registered trademark of Blue Ridge Fiberboard, Inc.

GenFlex Wood Fiber Roof Insulation

Quantity/ Units	Product	Item Code	Size	Pieces Per Bundle	Sq. Ft. Per Bundle	Weight Per Bundle	Bundles Per Truck	Square Feet per Truckload
	1/2" Wood Fiber "E" (Jarret, VA)	8501	4' x 4'	95	1520	973	44	66,880
		8502	4' x 8'	95	3,040	1,946	22	66,880
	1" Wood Fiber "E" (Jarret, VA)	8504	4' x 4'	48	768	907	44	33,792
		8505	4' x 8'	48	1,536	1,813	22	33,792
	1/2" Wood Fiber "B" (Intl' Falls, MN)	8501	4' x 4'	90	1,440	1,140	44	63,360
		8502	4' x 8'	90	2,880	2,300	22	63,360
	1" Wood Fiber "B" (Intl' Falls, MN)	8504	4' x 4'	45	720	1,120	44	45,760
		8505	4' x 8'	45	1,440	2,080	22	45,760

Availability: GenFlex Wood Fiber is manufactured in a number of strategically located facilities in order to provide prompt and efficient delivery throughout the United States.

Poly Bagging: All truckloads of Wood Fiber are shipped without poly bagging. Poly bags are available upon request for an additional charge.

Wood Fiber Freight Terms

- Freight allowed on truckload shipments of 1/2" and 1" wood fiber roof insulation for full truckloads only.
- For an additional charge, 1/2" 4' x 8' wood fiber roof insulation is inventoried in some GenFlex insulation plants and may be combined with ISO 95+ for prepaid shipments.
- 1" wood fiber roof insulation is not inventoried at any GenFlex location and is only shipped in full truckload quantities.

For additional order forms,
please visit www.genflex.com

Updated 06/29/15