

EPDM SOLVENT-FREE BONDING ADHESIVE



More coverage in less time...

- ▶ As a premier bonding adhesive, it allows contractors to do more work in less time
- ▶ Aids with projects that may have tighter constraints with manpower, logistics or regulations



FAST APPLICATION. NO SOLVENTS.



Features & Benefits

- ▶ **Non-Flammable & Non-Hazardous**
Contains no solvents, so it has NEAR ZERO grams per liter of volatile organic compounds.
- ▶ **Installation Speed**
With no waiting for flash-off and a single-sided wet lay application, labor time is cut in half. The adhesive has a uniformed mixture and the application allows contractors to mate the EPDM membrane as soon as the adhesive is applied.
- ▶ **Odorless and Safe**
Allows contractors to use it on occupied buildings and reduces fatigue related to toxic fumes.
- ▶ **Greater Coverage Area**
Has a coverage rate of 120-150 square feet per gallon, which is up to a 50% greater coverage rate than competitors' coverage of 100 square feet. In addition, it has significantly larger coverage rate than other LVOC products' 60-80 square feet. Based off of 40,000 sq. ft. application with 80 sq. ft. per gallon.
- ▶ **No Mixing**
Immediately start applying and will always hold a uniformed mixture.

COMPARISON GUIDE

Comparison Guide	EPDM Solvent-Free Bonding Adhesive	Leading Competitor	Water Based Bonding Adhesive P	All-Purpose Bonding Adhesive
Solvent-Free	✓	✓	--	--
No Mixing	✓	✓	--	--
No Odor	✓	✓	--	--
Apply Single Side	✓	✓	--	--
No Wait, Wet Lay	✓	✓	--	--
Visual Flash Off	NA	NA	✓	--
Coverage Rate	150 sq. ft.	100 sq. ft.	120 sq. ft.	60 sq. ft.
Lowest Apply Temperature	40 °F and rising	40 °F and rising	40 °F and rising	20 °F
VOC Content	NEAR ZERO g/L*	< 57 g/L	17 g/L	< 250 g/L

*When reacting with air, generates up to 16 g/L

PERFORMANCE

Property Minimum Performance	
Base Polymer	Synthetic
Color	Yellow
Brookfield Viscosity	6,000 to 10,000 Centipoises (CPS)
Weight/Gallon	8.3 to 8.5 Pounds/Gallon (0.9946 Kg/L to 1.0185 Kg/L)
Percent Solids	100%
Field Dispensing	Spray applied, drop spreadable, dip & roll with rollers
VOC Content	.1084 ± 0.0250 Pounds/Gallon (13 ± 3 Grams/Liter)

Coverage Area - Average Pails Per Job

