# SAFETY DATA SHEET



### 1. Identification

Product identifier GENFLEX EZ TPO Clear Cut Edge Sealant LVOC

Other means of identification

Product code W59TPOC01L

Recommended use Roofing and Architectural Sealant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

**Distributed by**GenFlex Roofing Systems an operating division of Firestone Building Products Company, LLC

Address 26 Century Boulevard, Suite 200

Nashville, TN 37214

Website www.genflex.com

Email genflexmsds@bfdp.com

Telephone Number Technical: 1-800-443-4272

**Emergency Telephone** 

Number

CHEMTREC: 1-800-424-9300

# 2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSensitization, skinCategory 1BReproductive toxicityCategory 2

Specific target organ toxicity, repeated

exposure

Category 2 (central nervous system)

Environmental hazards Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment,

long-term hazard

Category 2

Category 2

OSHA defined hazards Not classified.

Label elements

946390



Signal word Danger

Hazard statement Highly flammable liquid and vapor. May cause an allergic skin reaction. Suspected of damaging

fertility or the unborn child. May cause damage to organs (central nervous system) through

prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

**Precautionary statement** 

Version #: 01

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective

gloves/protective clothing/eye protection/face protection.

**Response** If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use foam,

carbon dioxide, dry powder or water fog to extinguish. Collect spillage.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Revision date: - Issue date: 19-October-2021

GENFLEX EZ TPO Clear Cut Edge Sealant LVOC

**Disposal** 

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	CAS number	%
4-Chlorobenzotrifluoride	98-56-6	60 - 65
Toluene	108-88-3	5 - <10

**Composition comments** 

All concentrations are in percent by weight unless otherwise indicated.

Components not listed are either non-hazardous or are below reportable limits.

#### 4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Narcosis. Behavioral changes. Decrease in motor functions. Direct contact with eyes may cause temporary irritation. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

**General information** 

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

#### 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

946390

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed such as: Carbon oxides (COx). Hydrogen chloride. Hydrogen fluoride.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. General fire hazards Highly flammable liquid and vapor.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Version #: 01

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Revision date: - Issue date: 19-October-2021

SDS US

# Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

## **Environmental precautions**

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

#### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. Take precautionary measures against static discharges.

# Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA	Table 7-2	(20 CED	1010 1000\
US. USITA	I able 2-2	しょう しょい	1310.10001

Components	Туре	Value	
Toluene (CAS 108-88-3)	Ceiling	300 ppm	
	TWA	200 ppm	
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
Toluene (CAS 108-88-3)	TWA	20 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	
Toluene (CAS 108-88-3)	STEL	560 mg/m3	
		150 ppm	
	TWA	375 mg/m3	
		100 ppm	

#### **Biological limit values**

ACGIH Biological Exposure Indices	<b>ACGIH</b>	<b>Biological</b>	<b>Exposure</b>	Indices
-----------------------------------	--------------	-------------------	-----------------	---------

Components	Value	Determinant	Specimen	Sampling Time
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

## US - California OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

## US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3)

Skin designation applies.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection** If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor

cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.
Form Liquid.

Color Clear. Colorless.

Odor Aromatic.
Odor threshold Not available.
pH Not determined.
Melting point/freezing point Not determined.
Initial boiling point and boiling 282.2 °F (139 °C)

range

Flash point 39.2 °F (4 °C)
Evaporation rate Not available.
Flammability (solid, gas) Not applicable.

Vapor densityNot determined.Relative densityNot determined.

Solubility(ies)

Solubility (water) Not determined.

Partition coefficient Not applicable, product is a mixture.

(n-octanol/water)

Auto-ignition temperature Not self-igniting.

**Decomposition temperature** Not applicable as the product is not unstable.

Viscosity2500 - 4500 cPViscosity temperature75.2 °F (24 °C)Other informationSolids: 25 - 28%

Density 1.18 g/ml

SDS US

9.8 lb/gal

Explosive properties Not explosive.

Kinematic viscosity Not determined.

Oxidizing properties Not oxidizing.

VOC < 250 g/l

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Narcosis. Behavioral changes. Decrease in motor functions. May cause an allergic skin reaction.

Dermatitis. Rash. Direct contact with eyes may cause temporary irritation.

## Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components Species Test Results

4-Chlorobenzotrifluoride (CAS 98-56-6)

Acute

**Dermal** 

LD50 Rabbit > 3300 mg/kg bw/day

Inhalation

LC50 Rat > 32.03 mg/l, 4 hours

Oral

LD50 Rat 5546 mg/kg bw/day (Male)

Toluene (CAS 108-88-3)

Acute

Dermal

LD50 Rabbit 12200 mg/kg

Inhalation

Vapor

LC50 Rat 28.1 mg/l, 4 Hours

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

GENFLEX EZ TPO Clear Cut Edge Sealant LVOC

SDS US

946390 Version #: 01 Revision date: - Issue date: 19-October-2021

IARC Monographs. Overall Evaluation of Carcinogenicity

4-Chlorobenzotrifluoride (CAS 98-56-6)

Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

**NTP Report on Carcinogens** 

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Suspected of damaging fertility or the unborn child. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Fish

May cause damage to organs (central nervous system) through prolonged or repeated exposure.

2B Possibly carcinogenic to humans.

**Aspiration hazard** Not an aspiration hazard.

12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Components **Test Results** Species 4-Chlorobenzotrifluoride (CAS 98-56-6) Aquatic Acute Fish LC50 Fish 3 mg/l, 96 hours Toluene (CAS 108-88-3) Aquatic Acute EC50 Daphnia magna 11.5 ma/l. 48 hours Crustacea Fish LC50 Oncorhynchus kisutch 5.5 mg/l, 96 hours Chronic NOEC Crustacea Ceriodaphnia dubia 0.74 mg/l, 7 days

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential No data available for this product.

Partition coefficient n-octanol / water (log Kow)

4-Chlorobenzotrifluoride (CAS 98-56-6) 3.6 Toluene (CAS 108-88-3) 2.73

NOEC

Bioconcentration factor (BCF)

4-Chlorobenzotrifluoride (CAS 98-56-6) 121 - 202

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

Oncorhynchus kisutch

potential.

13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

> material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in

1.4 mg/l, 40 days

accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

## 14. Transport information

DOT

UN number UN1133 UN proper shipping name Adhesives

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group II
Environmental hazards

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 149, B52, IB2, T4, TP1, TP8

Packaging exceptions 150
Packaging non bulk 173
Packaging bulk 242

**IATA** 

UN number UN1133 UN proper shipping name Adhesives

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards Yes
ERG Code 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IMDG** 

**UN number** UN1133 **UN proper shipping name** ADHESIVES

Transport hazard class(es)
Class 3
Subsidiary risk Packing group ||

**Environmental hazards** 

Marine pollutant Yes EmS F-E, S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not established.

4-Chlorobenzotrifluoride (CAS 98-56-6) 0.1 % One-Time Export Notification only.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Toluene (CAS 108-88-3) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

**Toxic Substances Control Act (TSCA)** 

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)

Respiratory or skin sensitization

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Toluene	108-88-3	5 - <10

## Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Toluene (CAS 108-88-3)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

# Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3) 6594

## Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 %WV

### **DEA Exempt Chemical Mixtures Code Number**

Toluene (CAS 108-88-3) 594

### **US** state regulations

#### **US. Massachusetts RTK - Substance List**

Toluene (CAS 108-88-3)

#### US. New Jersey Worker and Community Right-to-Know Act

4-Chlorobenzotrifluoride (CAS 98-56-6)

Toluene (CAS 108-88-3)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Toluene (CAS 108-88-3)

### **US. Rhode Island RTK**

Toluene (CAS 108-88-3)

### **California Proposition 65**



WARNING: This product can expose you to Toluene, which is known to the State of California to cause birth

defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

## California Proposition 65 - CRT: Listed date/Carcinogenic substance

4-Chlorobenzotrifluoride (CAS 98-56-6) Listed: June 28, 2018

#### California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

4-Chlorobenzotrifluoride (CAS 98-56-6)

Toluene (CAS 108-88-3)

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

GENFLEX EZ TPO Clear Cut Edge Sealant LVOC

Country(s) or region Inventory name On inventory (yes/no)\*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

16. Other information, including date of preparation or last revision

Issue date 19-October-2021

**Revision date** 

country(s).

Version # 01

**HMIS®** ratings Health: 2\*

Flammability: 3 Physical hazard: 0

**Disclaimer** Firestone Building Products Company, LLC cannot anticipate all conditions under which this

information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper

use. The information in the sheet was written based on the best knowledge and experience

currently available.

SDS US 946390 Version #: 01 Revision date: - Issue date: 19-October-2021