

1. Identification

Product identifier	GenFlex All Purpose LVOC Primer
Other means of identification	
Product code	W590030119
Recommended use	Construction. Primer.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Distributed by	Holcim Solutions and Products US, LLC
Address	26 Century Boulevard, Suite 205 Nashville, TN 37214 GenFlex™ is a Holcim Solutions and Products US, LLC brand
Website	Genflex.com
Telephone Number	Technical: 1-800-443-4272
Emergency Telephone Number	For Chemical Emergency, Spill, Leak, Fire, Exposure, or Incident: CHEMTREC within USA and Canada: 1-800-424-9300 CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Sensitization, respiratory	Category 1
	Sensitization, skin	Category 1
	Carcinogenicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause drowsiness or dizziness. Suspected of causing cancer. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Take off contaminated clothing and wash it before reuse. In case of fire: Use carbon dioxide, dry powder; water fog (large fires) to extinguish. Collect spillage.

Storage

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
4-Chlorobenzotrifluoride	98-56-6	45 - 70
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	10 - 25
Acetone	67-64-1	7 - 13
Polymethylene polyphenylene isocyanate	9016-87-9	< 0.5

Composition comments

All concentrations are in percent by weight unless otherwise indicated. Components not listed are either non-hazardous or are below reportable limits. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a poison center or doctor/physician.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Larger fires: Dry powder. Carbon dioxide (CO ₂). Water fog. Small fires: Dry powder. Carbon dioxide (CO ₂). Dry sand.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed such as: Carbon oxides (CO _x). Hydrogen Chloride (HCl). Hydrocarbons.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m ³ 1000 ppm

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)	PEL	400 mg/m ³
		100 ppm

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Acetone (CAS 67-64-1)	IDLH	2.5 %
		2500 ppm
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)	IDLH	1 %
		1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m ³
		250 ppm
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)	TWA	400 mg/m ³
		100 ppm

Biological limit values**ACGIH Biological Exposure Indices (BEI)**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear approved chemical safety goggles.

Skin protection**Hand protection**

Wear appropriate chemical resistant gloves. Examples of acceptable glove barrier materials include: Nitrile butyl rubber (NBR). Fluoroelastomer (FKM). Polyethylene/Ethylene Vinyl Alcohol (PE/EVAL). Suitable gloves can be recommended by the glove supplier.

Skin protection**Other**

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor cartridge and full facepiece. Appropriate respirator selection should be made by a qualified professional.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties**Appearance**

Physical state Liquid.

Form Liquid.

Color Amber.

Odor Characteristic.

Odor threshold Not available.

pH Not applicable as the product is insoluble in water.

Melting point/freezing point Not determined.

Initial boiling point and boiling range 133 °F (56.11 °C)

Flash point -4 °F (-20 °C)

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 2.6

Explosive limit - upper (%) 13

Vapor pressure 233 hPa (68 °F (20 °C))
174.8 mm Hg (68 °F (20 °C))

Vapor density Not determined.

Relative density 1.01

Solubility(ies)

Solubility (water) Insoluble (in water).

Partition coefficient (n-octanol/water) Not applicable, product is a mixture.

Auto-ignition temperature Not self-igniting

Decomposition temperature Not applicable as the product is not unstable.

Viscosity ≤ 200 cps (#2 Spindle @ 20 rpm)

Other information Ignition temperature: 465.0 °C (869 °F)

Density Not determined.

Explosive properties Not explosive.

Kinematic viscosity Not determined.

Oxidizing properties Not oxidizing.

VOC 232 g/l SCAQMD 1168 Method

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Strong bases.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
4-Chlorobenzotrifluoride (CAS 98-56-6)		
Acute		
Dermal		
LD50	Rabbit	> 3300 mg/kg bw/day
Inhalation		
LC50	Rat	> 32.03 mg/l, 4 hours
Oral		
LD50	Rat	5546 mg/kg bw/day (Male)
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Rabbit	> 15700 mg/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	76 mg/l, 4 Hours
Oral		
LD50	Rat	5800 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)		
Acute		
Dermal		
LD50	Rat	> 2920 mg/kg
Inhalation		
LC50	Rat	> 23300 mg/m ³
Oral		
LD50	Rat	> 5840 mg/kg
Polymethylene polyphenylene isocyanate (CAS 9016-87-9)		
Acute		
Dermal		
LD50	Rabbit	> 10000 mg/kg
Inhalation		
<i>Mist</i>		
LC50	Rat	> 490 mg/m ³ , 4 Hours
Oral		
LD50	Rat	> 10000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	

Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Suspected of causing cancer.
IARC Monographs. Overall Evaluation of Carcinogenicity	
4-Chlorobenzotrifluoride (CAS 98-56-6)	2B Possibly carcinogenic to humans.
Polymethylene polyphenylene isocyanate (CAS 9016-87-9)	3 Not classifiable as to carcinogenicity to humans.
NTP Report on Carcinogens	
Not listed.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)	
Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure	Not classified. Based on available data, the classification criteria are not met.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components		Species	Test Results
4-Chlorobenzotrifluoride (CAS 98-56-6)			
Aquatic			
<i>Acute</i>			
Fish	LC50	Fish	3 mg/l, 96 hours
Acetone (CAS 67-64-1)			
Aquatic			
<i>Acute</i>			
Crustacea	LC50	Daphnia pulex	8800 mg/l, 48 Hours
Fish	LC50	Pimephales promelas	7163 mg/l, 96 Hours
<i>Chronic</i>			
Crustacea	NOEC	Daphnia magna	> 79 mg/l, 21 days

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available for this product.

Partition coefficient n-octanol / water (log Kow)

4-Chlorobenzotrifluoride (CAS 98-56-6)	3.6
Acetone (CAS 67-64-1)	-0.24
Bioconcentration factor (BCF)	
4-Chlorobenzotrifluoride (CAS 98-56-6)	121 - 202

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	
Marine pollutant	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	149, B52, IB2, T4, TP1, TP8
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

IATA

UN number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	Yes.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN1133
UN proper shipping name	ADHESIVES
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	Yes.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

4-Chlorobenzotrifluoride (CAS 98-56-6) 0.1 % One-Time Export Notification only.

TSCA Chemical Action Plans, Chemicals of Concern

Polymethylene polyphenylene isocyanate (CAS 9016-87-9) Methylene Diphenyl Diisocyanate (MDI) And Related Compounds Action Plan [RIN 2070-ZA15]

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Listed.
(CAS 64742-49-0)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

All components are either listed on the TSCA 8(b) inventory and designated "active" or exempt from listing.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitization
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Acetone (CAS 67-64-1) Low priority

US state regulations

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)

US. New Jersey Worker and Community Right-to-Know Act

4-Chlorobenzotrifluoride (CAS 98-56-6)
Acetone (CAS 67-64-1)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)
Polymethylene polyphenylene isocyanate (CAS 9016-87-9)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

US. Rhode Island RTK

Acetone (CAS 67-64-1)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)

California Proposition 65



WARNING: This product can expose you to 4-Chlorobenzotrifluoride, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

4-Chlorobenzotrifluoride (CAS 98-56-6) Listed: June 28, 2018

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

4-Chlorobenzotrifluoride (CAS 98-56-6)
Acetone (CAS 67-64-1)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)
Polymethylene polyphenylene isocyanate (CAS 9016-87-9)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 08-December-2022

Revision date 02-August-2023

Version # 02

HMIS® ratings Health: 3*
Flammability: 3
Physical hazard: 0

Disclaimer Holcim Solutions and Products US, LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.