

## 1. Identification

<b>Product identifier</b>	<b>GenFlex Cleaner (Produced @ Michigan Center MI plant)</b>	
<b>Other means of identification</b>		
<b>Product code</b>	W590010092	
<b>Recommended use</b>	Construction. Cleaner.	
<b>Recommended restrictions</b>	None known.	
<b>Manufacturer/Importer/Supplier/Distributor information</b>		
<b>Distributed by</b>	Holcim Solutions and Products US, LLC	
<b>Address</b>	26 Century Boulevard, Suite 205 Nashville, TN 37214 GenFlex™ is a Holcim Solutions and Products US, LLC brand	
<b>Website</b>	Genflex.com	
<b>Telephone Number</b>	Technical: 1-800-443-4272	
<b>Emergency Telephone Number</b>	For Chemical Emergency, Spill, Leak, Fire, Exposure, or Incident:  CHEMTREC within USA and Canada: 1-800-424-9300 CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)	

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable liquids	Category 2
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



<b>Signal word</b>	Danger
<b>Hazard statement</b>	Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. Toxic to aquatic life with long lasting effects.
<b>Precautionary statement</b>	
<b>Prevention</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

<b>Response</b>	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.
<b>Storage</b>	Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	None.

### 3. Composition/information on ingredients

#### Substances

Chemical name	CAS number	%
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	100*
Distillates (petroleum), light distillate hydrotreating process, low-boiling	68410-97-9	100*
Solvent naphtha (petroleum), light aliph.	64742-89-8	100*

#### Constituents

Chemical name	Common name and synonyms	CAS number	%
Heptane		142-82-5	5 - 10
Octane		111-65-9	5 - 10
Toluene		108-88-3	0 - 0.1

**Composition comments** \* Product is one of the following: CAS 64742-49-0, CAS 68410-97-9 or CAS 64742-89-8. All concentrations are in percent by weight. Occupational Exposure Limits for constituents are listed in Section 8.

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
<b>Skin contact</b>	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Foam. Dry chemical powder. Carbon dioxide (CO2). Water fog.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed such as: Carbon oxides (COx).

<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Highly flammable liquid and vapor.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

**Precautions for safe handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities** Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Material	Type	Value	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	PEL	400 mg/m3	
		100 ppm	
Components	Type	Value	Form
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 68410-97-9)	PEL	5 mg/m3	Mist.
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)	PEL	400 mg/m3	
		100 ppm	

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-89-8)	PEL	400 mg/m3	
		100 ppm	
Constituents	Type	Value	
Heptane (CAS 142-82-5)	PEL	2000 mg/m3	
		500 ppm	
Octane (CAS 111-65-9)	PEL	2350 mg/m3	
		500 ppm	

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 68410-97-9)	TWA	5 mg/m3	Inhalable fraction.
Constituents	Type	Value	
Heptane (CAS 142-82-5)	STEL	500 ppm	
		TWA	400 ppm
Octane (CAS 111-65-9)	TWA	300 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Material	Type	Value	
Heptane	TWA	400 mg/m3	
		100 ppm	
Components	Type	Value	Form
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 68410-97-9)	STEL	10 mg/m3	Mist.
		TWA	Mist.
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)	TWA	400 mg/m3	
		100 ppm	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-89-8)	TWA	400 mg/m3	
		100 ppm	
Constituents	Type	Value	
Heptane (CAS 142-82-5)	Ceiling	1800 mg/m3	
		440 ppm	
	TWA	350 mg/m3	
		85 ppm	
Octane (CAS 111-65-9)	Ceiling	1800 mg/m3	
		385 ppm	
	TWA	350 mg/m3	
		75 ppm	

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

## Exposure guidelines

### US - California OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

### US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3)

Skin designation applies.

## Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

## Individual protection measures, such as personal protective equipment

### Eye/face protection

Wear safety glasses with side shields (or goggles).

### Skin protection

#### Hand protection

Wear appropriate chemical resistant gloves. Examples of preferred glove barrier materials include: Fluoroelastomer (FKM). Ethyl vinyl alcohol laminate ("EVAL"). Suitable gloves can be recommended by the glove supplier.

#### Skin protection

##### Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

### Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor cartridge and full facepiece. Appropriate respirator selection should be made by a qualified professional.

### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

## General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

#### Physical state

Liquid.

#### Form

Liquid.

#### Color

Clear, colorless.

### Odor

Hydrocarbon.

### Odor threshold

Not available.

### pH

Not determined; product is not soluble in water.

### Melting point/freezing point

< -76 °F (< -60 °C)

### Initial boiling point and boiling range

> 244.4 - < 302 °F (> 118 - < 150 °C)

### Flash point

> 57.2 - < 64.4 °F (> 14 - < 18 °C) Closed Cup

### Evaporation rate

< 1 (Butyl acetate = 1)

### Flammability (solid, gas)

Not applicable.

### Upper/lower flammability or explosive limits

#### Explosive limit - lower (%)

0.9 % v/v

#### Explosive limit - upper (%)

7.6 % v/v

### Vapor pressure

> 11 - < 16 mm Hg (68 °F (20 °C))

### Vapor density

> 4 (Air = 1) (> 68 - < 77 °F (> 20 - < 25 °C))

### Relative density

> 0.74 - < 0.76 (Water = 1) (60.08 °F (15.6 °C))

### Solubility(ies)

#### Solubility (water)

Insoluble

### Partition coefficient (n-octanol/water)

Not determined.

### Auto-ignition temperature

> 474.8 - < 878 °F (> 246 - < 470 °C)

<b>Decomposition temperature</b>	Not applicable as the product is not unstable.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	0.7601 g/cm <sup>3</sup> (60.1 °F (15.6 °C))
<b>Explosive properties</b>	Not explosive.
<b>Kinematic viscosity</b>	< 0.01 mm <sup>2</sup> /s (104 °F (40 °C))
<b>Molecular formula</b>	UVCB
<b>Oxidizing properties</b>	Not oxidizing.
<b>VOC</b>	> 743 - < 755 g/l > 6.2 - < 6.3 lb/gal

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**Symptoms related to the physical, chemical and toxicological characteristics**      Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain.

### Information on toxicological effects

**Acute toxicity**      Not expected to be acutely toxic.

### Toxicological data

Constituents	Species	Test Results
Heptane (CAS 142-82-5)		
<b>Acute</b>		
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Rat	> 29.29 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	15000 mg/kg

**Skin corrosion/irritation**      Causes skin irritation.

**Serious eye damage/eye irritation**      Direct contact with eyes may cause temporary irritation.

### Respiratory or skin sensitization

**Respiratory sensitization**      Not a respiratory sensitizer.

**Skin sensitization**      This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**      No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity**      Not classifiable as to carcinogenicity to humans.

## IARC Monographs. Overall Evaluation of Carcinogenicity

Distillates (petroleum), light distillate hydrotreating process, low-boiling (CAS 68410-97-9) 3 Not classifiable as to carcinogenicity to humans.  
Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

## NTP Report on Carcinogens

Not listed.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

**Reproductive toxicity** Suspected of damaging fertility or the unborn child.  
**Specific target organ toxicity - single exposure** May cause drowsiness and dizziness.  
**Specific target organ toxicity - repeated exposure** Not classified.  
**Aspiration hazard** May be fatal if swallowed and enters airways.  
**Chronic effects** Prolonged inhalation may be harmful.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Constituents	Species	Test Results
Octane (CAS 111-65-9)		
<b>Aquatic</b>		
Crustacea	LC50 Daphnia magna	0.38 mg/l, 48 hours

**Persistence and degradability** Expected to be inherently biodegradable.  
**Bioaccumulative potential** The product is not bioaccumulating.  
**Mobility in soil** No data available.  
**Other adverse effects** The product contains volatile organic compounds which have a photochemical ozone creation potential.

## 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.  
**Local disposal regulations** Dispose in accordance with all applicable regulations.  
**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.  
**Waste from residues / unused products** Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).  
**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

### DOT

**UN number** UN1268  
**UN proper shipping name** Petroleum products, n.o.s.  
**Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**Label(s)** 3  
**Packing group** II  
**Environmental hazards**  
**Marine pollutant** Yes.  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Special provisions** 144, IB2, T7, TP1, TP8, TP28  
**Packaging exceptions** 150

Packaging non bulk 202  
Packaging bulk 242

#### IATA

UN number UN1268  
UN proper shipping name Petroleum products, n.o.s.  
Transport hazard class(es)  
Class 3  
Subsidiary risk -  
Packing group II  
Environmental hazards Yes.  
ERG Code 3H  
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

#### IMDG

UN number UN1268  
UN proper shipping name PETROLEUM PRODUCTS, N.O.S.  
Transport hazard class(es)  
Class 3  
Subsidiary risk -  
Packing group II  
Environmental hazards  
Marine pollutant Yes.  
EmS F-E, S-E  
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Heptane (CAS 142-82-5)	Listed.
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)	Listed.
Octane (CAS 111-65-9)	Listed.
Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	Listed.
Toluene (CAS 108-88-3)	Listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

**Toxic Substances Control Act (TSCA)** This substance is on the TSCA 8(b) inventory and is designated "active".

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

##### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** Yes

**Classified hazard categories** Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard

##### SARA 313 (TRI reporting)

Not regulated.



## Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Toluene (CAS 108-88-3)

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

### Safe Drinking Water Act (SDWA)

Not regulated.

### Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3) 6594

### Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 %WV

### DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3) 594

## US state regulations

### US. Massachusetts RTK - Substance List

Distillates (petroleum), light distillate hydrotreating process, low-boiling (CAS 68410-97-9)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)

Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

### US. New Jersey Worker and Community Right-to-Know Act

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)

Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

### US. Pennsylvania Worker and Community Right-to-Know Law

Distillates (petroleum), light distillate hydrotreating process, low-boiling (CAS 68410-97-9)

### US. Rhode Island RTK

Distillates (petroleum), light distillate hydrotreating process, low-boiling (CAS 68410-97-9)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)

Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

### California Proposition 65



**WARNING:** This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987

Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004

Naphthalene (CAS 91-20-3) Listed: April 19, 2002

### California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

Toluene (CAS 108-88-3) Listed: January 1, 1991

### California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), light distillate hydrotreating process, low-boiling (CAS 68410-97-9)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)

Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 27-January-2023

**Revision date** -

**Version #** 01

**HMIS® ratings**  
 Health: 3\*  
 Flammability: 3  
 Physical hazard: 0

**Disclaimer** Holcim Solutions and Products US, LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.